

1008072200

IP Heavy Duty Telephone, Door, Full Keyboard



Industrial Intercom



IP66



IK10

DESCRIPTION

- Compatible with Vingtor-Stentofon AlphaCom, Vingtor-Stentofon Pulse and iPBXs (SIP)
- Four variants: Full keyboard and hotline (no keyboard), both with or without door
- Made for critical communication in rough environments like roads, tunnels, ships
- Water and dust resistant (IP66)
- Very durable with 5 mm aluminum casing and stainless steel components
- Magnetic reed hook-switch ensures minimal wear and tear
- Supports VoIP with SIP and STENTOFON CCoIP with AlphaCom XE
- Option for GSM cellular connectivity
- Support local power and Power over Ethernet (PoE)
- Integrated data switch with advanced networking and security functions
- Supports HD Voice
- Advanced supervision functions

The Vingtor-Stentofon IP Heavy Duty Telephone is made for environments that need a telephone which can withstand rough usage and treatment. The telephone is well suited for heavy duty usage due to the thick aluminum casing, stainless steel materials, and high ingress protection (IP66).

The IP telephone supports open standards and is compatible with Vingtor-Stentofon AlphaCom, Vingtor-Stentofon Pulse and iPBXs using SIP technology. When working in AlphaCom mode, the IP telephone supports special services only available using the Vingtor-Stentofon CCoIP protocol, AlphaCom server. Examples of services are emergency broadcast with volume override, CCTV integration, call priority, and AlphaNet multisite networking and Vingtor-Stentofon event scripting.

The station provides high quality conversations, using HD Voice and Vingtor-Stentofon's superb audio technology such as active noise filtering, echo cancellation, wide band audio codec and high power audio outputs.

The telephone has an integrated managed data switch providing advanced networking and security features. The integrated switch provides support for:

- Protection from unwanted access
- Quality of Service (QoS) by managing data traffic
- Increased system availability by redundant LAN infrastructure
- Cost-efficient installation by providing shared network connections through the integrated data switch

As a result, instant, efficient, and secure delivery of voice and data services in an IP environment is ensured. The station has one relay and one logical output. These outputs can, for instance, be used to turn on a strobe light. The operation of the outputs is programmable. To provide maximum availability, the station comes with advanced supervision functions. The station linetest will detect if there are any faults in the network or station electronics. The status of the station is reported to AlphaWeb as well as to 3rd party management systems using SNMP, Syslog or OPC.

SPECIFICATIONS

GENERAL

Dimensions (WxHxD)	205 x 320 x 148 mm
Weight	5.4 kg
Ingress protection	IP66
Impact protection	IK10
Construction	5 mm aluminum casing and stainless steel components
Mounting	Wall mounted
Temperature	-40°C to +60°C
Relative humidity	0% – 95%
Frequency range	200 – 7000 Hz
Remote control, Max switching capacity, Max voltage relay, Max current relay	3 digital inputs, 1 relay, 30W DC , 60V DC, 1ADC
SIP support	RFC 3261, SIP Info (DTMF), RFC 2833 (DTMF)
IP protocols	IP v4 - TCP - UDP - HTTPS - TFTP - RTP - RTCP - DHCP - SNMP DiffServ - TOS - STENTOFON CCoIP® - SIP
LAN protocols	Power over Ethernet (IEEE 802.3 a-f), VLAN (IEEE 802.1pq)*, Network Access Control (IEEE 802.1x)*, STP (IEEE 802.1d), RSTP (IEEE 802.1d-2004)
Audio technology	HD Voice 200 Hz – 7 kHz (G.722), Telephony 3.4 kHz (G.711), Active noise filtering, Echo cancellation, Open duplex, Adaptive jitter filter, 1.5 Watt audio output
Power	Power over Ethernet (IEEE 802.3 a-f), Class 0, Local power 19 – 27V DC, Idle 2.5W, max. 4.5W
Management and operation	HTTPS (Web configuration), DHCP and static IP, TFTP (firmware and configuration download), SNMP (monitoring)
Compliance	CE and FCC Part 15

[Export Table Data](#)

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1008072100	Heavy Duty IP Telephone, full keyboard	5.0 kg
1008072120	Heavy Duty IP Telephone, hotline	5.0 kg
1008072200	Heavy Duty IP Telephone, door, full keyboard	5.4 kg
1008072220	Heavy Duty IP Telephone, door, hotline	5.4 kg
Supplementary equipment:		
2200003000	GSM Media Gateway	1.2 kg
1020600992	IRR-3 Relaybox 24V DC or 220V AC - Signal Unit	0.35 kg

[Export Table Data](#)

ACCESSORIES



IRR-3

Item number: 1020600992

Created: 09.03.2015, updated: 05.09.2018

page 3/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Vingtor-Stentofon products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel – All rights reserved.